


# GREY EDITION



**Colouring:**

fetra transport equipment in this colour combination fits perfectly into modern work environments. The powder coating in anthracite grey RAL 7016 is simple and timeless.



**Platform:**

The derived timber material boards in medium grey are insensitive to dirt and look particularly elegant matching the innovative fetra easy-running TPE-castors.



**TPE castor:**

The innovative easy-running TPE-castor in the attractive fetra design is non-marking and odourless. Particularly smooth-running groove ball bearing.



Table top cart **2402/7016**



**Dollies and collapsible carts**

made of tubular steel welded and powder coated, anthracite grey RAL 7016, with tubular steel, sheet wooden platform, handles bolted on, 2 swivel and 2 fixed-wheel castors, TPE tyres, hubs groove ball bearing.

Swivel castors with wheel locks.

**1161/7016\***

Platform made of derived timber material boards housed in the frames, surface grey.

**1164/7016**

Dollies made of tubular steel welded and powder coated, anthracite grey RAL 7016, with platform made of wooden, handles bolted on.

Capacity upper shelf 100 kg.

**1132/7016 | 1154/7016**

Handlebar foldable onto platform.

Loading height with wheel-Ø 125 mm: 205 mm  
wheel-Ø 160 mm: 230 mm

**1200/7016 | 1202/7016**

Loading height with wheel-Ø 125 mm: 206 mm

**Open Carts  
Modular system**

**2500/7016 - 2503/7016**

Tubular steel and profile steel welded, powder coated, surface durably protected, resistant to impact and scratches. Platform made of derived timber material boards, surface grey.

2 swivel and 2 fixed-wheel castors, TPE tyres, 160 x 40 or 200 x 40 mm, hubs with groove ball bearing or pneumatic tyres 220 x 70 mm (additional charge).

Swivel castors with wheel locks.

Height of loading platform:

TPE 160 Ø = 228 mm

TPE 200 Ø = 270 mm

Pneumatic tyres 220 Ø = 285 mm

\*Can not be fitted with TOTALSTOP.

**Accessories  
on pages 183-185**



1161/7016\*



1164/7016



1132/7016 | 1154/7016



1200/7016 | 1202/7016



2500/7016 - 2503/7016

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Net weight kg	
<b>Dollies</b>	1161/7016*	250	125	600 x 500	890 x 500 x 860	11	
	1164/7016	250	125	600 x 450	860 x 450 x 875	19	
<b>Collapsible carts</b>	1132/7016	250	125	720 x 450	815 x 470 x 930	15	
	1154/7016	250	160	900 x 600	995 x 620 x 965	24	
<b>Storeroom trolleys</b>	1200/7016	250	125	850 x 450	1100 x 450 x 910	15	
	1202/7016	250	125	1000 x 600	1250 x 600 x 910	19	
<b>Open carts</b>	2500/7016	500	160	850 x 500	975 x 509 x 948	23	
	2501/7016	600	200	1000 x 600	1125 x 609 x 990	27	
	2502/7016	600	200	1000 x 700	1125 x 709 x 990	30	
	2503/7016	600	200	1200 x 800	1325 x 809 x 990	35	



2740/7016 | 2742/7016



2750/7016 | 2752/7016



4820/7016 | 4822/7016



4830/7016 | 4832/7016



**Tablet holder**  
For details see page 185.



**Scanner holder**  
For details see page 185.



**Light table top carts**

2740/7016 | 2742/7016  
2750/7016 | 2752/7016

Table top carts, tubular steel welded and powder coated anthracite grey RAL 7016, surface durably protected, resistant to impact and scratches, shelves made of derived timber material boards, in a frame of angle steel, height of rim 12 mm, with a high push bar.

2 swivel and 2 fixed-wheel castors with TPE tyres, hubs with groove ball bearing.

Swivel castors with wheel locks.

Capacity upper and middle shelf 80 kg.

**Table top carts with trays**

4820/7016 | 4822/7016  
4830/7016 | 4832/7016

Table top cart, steel construction, welded. Tubular steel hoop and steel plate trays screwed. Trays oil-tight, rim 40 mm high, powder coated anthracite grey RAL 7016.

2 swivel and 2 fixed-wheel castors with TPE tyres, hubs with groove ball bearing.

Swivel castors with wheel locks.

Capacity upper and middle shelf 200 kg.

	Order-Nr.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Shelf heights mm	Net weight kg
<b>Table top carts</b>	2740/7016	300	125	850 x 500	986 x 511 x 1039	200, 820	28
	2742/7016	300	125	1000 x 600	1136 x 611 x 1039	200, 820	36
	2750/7016	300	125	850 x 500	986 x 511 x 1039	200, 510, 820	35
	2752/7016	300	125	1000 x 600	1136 x 611 x 1039	200, 510, 820	49
<b>Table top carts with trays</b>	4820/7016	400	160	850 x 500	1021 x 500 x 870	207, 829	36
	4822/7016	400	200	1000 x 700	1171 x 700 x 910	248, 870	47
	4830/7016	400	160	850 x 500	1021 x 500 x 870	207, 519, 829	46
	4832/7016	400	200	1000 x 700	1171 x 700 x 910	248, 560, 870	61

**Accessories**  
on pages 183-185



**MultiVario-  
Heavy table top carts  
Modular System**

Tubular steel and sectional steel, welded and powdercoated, surface durably protected, resistant to impact and scratches, shelves made of derived timber material boards, surface grey. 2 swivel and 2 fixed-wheel castors with TPE tyres 160 x 40 mm resp. 200 x 40 mm. Swivel castors with wheel locks.

**2496/7016**

Square platforms  
600 x 600 mm.  
**2 shelves**  
Capacity upper platform  
200 kg.

**2416/7016**

as 2496/7016, but with 3 shelves.  
Capacity upper and middle shelf 200 kg.

**2400/7016 - 2403/7016**

as 2496/7016, but rectangular platforms in 4 sizes.

**Super-MultiVario  
Heavy table top carts**

is especially designed for heavy loads. High-quality elasticated solid-rubber wheels and hubs with ball bearings guarantee an extreme manoeuvrability and a smooth run. Steel tube and sectional steel welded, powder coated, grey RAL 7016. Platforms made of antislip waterproof plywood boards (insert type of board). 2 swivel and 2 fixed-wheel castors, elasticated solid rubber tyres 200 x 50 mm, blue-grey „trackless“ hubs with ball bearings.

**12497/7016**

Square platforms  
700 x 700 mm.  
**2 shelves**  
Capacity upper platform  
500 kg.

**12402/7016 -  
12406/7016**

as 12497/7016, but rectangular platforms in 4 sizes.

\*Can not be fitted with FIXSTOP.

**Accessories  
on pages 183-185**



2496/7016



2416/7016



2400/7016 - 2403/7016



12497/7016\*



12402/7016 - 12406/7016\*

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Shelf heights mm	Net weight kg
<b>Table top carts</b>	2496/7016	500	160	600 x 600	737 x 609 x 860	228, 860	32
	2416/7016	500	160	600 x 600	737 x 609 x 860	228, 544, 860	44
	2400/7016	500	160	850 x 500	1047 x 509 x 860	228, 860	36
	2401/7016	600	200	1000 x 600	1197 x 609 x 900	270, 900	44
	2402/7016	600	200	1000 x 700	1197 x 709 x 900	270, 900	49
	2403/7016	600	200	1200 x 800	1397 x 809 x 900	270, 900	58
<b>Table top carts</b>	12497/7016*	1200	200	700 x 700	910 x 700 x 925	283, 925	54
	12402/7016*	1200	200	1000 x 700	1210 x 700 x 925	283, 925	67
	12403/7016*	1200	200	1200 x 800	1410 x 800 x 925	283, 925	77
	12405/7016*	1200	200	1600 x 800	1810 x 800 x 925	283, 925	100
	12406/7016*	1200	200	2000 x 800	2210 x 800 x 925	283, 925	156



2450/7016



12450/7016



2452/7016



12452/7016



2456/7016



12456/7016



**Drawer subdivision-set**

made of galvanized steel sheet, insertable. 1 longitudinal partition and 4 dividing sheets.

**Workshop carts**

Steel construction.  
Worktop composite panel 20 mm.  
2 swivel and 2 fixed-wheel castors, TPE tyres 160 x 40 mm, swivel castors wheels with lock.  
Powder coated, carcass grey RAL 7035, front anthracite grey RAL 7016.  
For technical reasons relating to transport the working platform the worktop and the wheels are not mounted. Easy self assembly.  
Capacity per shelf 80 kg.

**2450/7016**

With 1 cupboard, 1 fixed and 2 adjustable shelves, and drawers with ball bearing slide. Centrally lockable by cylinder lock.  
6 drawers  
H x W x D: 95 x 280 x 470 mm  
Capacity per drawer 35 kg.

**2452/7016**

With 1 cupboard, 1 fixed and 2 adjustable shelves, and drawers with ball bearing slide. Centrally lockable by cylinder lock.  
4 drawers  
H x W x D  
1 pc. 105 x 280 x 470 mm  
2 pcs. 160 x 280 x 470 mm  
1 pc. 210 x 280 x 470 mm  
Capacity per drawer 35 kg.

**2456/7016**

With 1 cupboard with double door without separation wall. 2 adjustable shelves. Doors centrally lockable by cylinder lock. Maximum opening angle 120°. Useful depth: 873 mm  
Useful width: 465 mm  
Opening width: 784 mm

**12450/7016 |**

**12452/7016 |**

**12456/7016**

Workshop carts with skirting on three sides 80 mm high, made of powder coated steel sheet.

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Net weight kg
Workshop carts	2450/7016	400	160	985 x 590	1080 x 590 x 915	66
	2452/7016	400	160	985 x 590	1080 x 590 x 915	62
	2456/7016	400	160	985 x 590	1080 x 590 x 915	48
Workshop carts with skirting	12450/7016	400	160	985 x 590	1080 x 590 x 995	71
	12452/7016	400	160	985 x 590	1080 x 590 x 995	67
	12456/7016	400	160	985 x 590	1080 x 590 x 995	53
Drawer subdivison set	2146	-	-	-	-	-



**Pallet Dollies**

For pallets and lattice boxes. Sturdy sectional steel construction with 4 catch corners for stacking, powder coated, anthracite grey RAL 7016. 2 swivel and 2 fixed-wheel castors. Castors with wheel lock.

**22801/7016**

**Capacity 750 kg**

TPE tyres 200 x 40 mm, hubs with ball bearings. Very low starting, rolling and swivelling resistance. Tyres are non-marking (trackless). Low-noise running on even flooring.



22801/7016



22881/7016

**22881/7016**

**Capacity 1050 kg**

Polyamide wheels 200 x 50 mm, hubs with roller bearings. Low rolling resistance, high chemical resistance, non marking. Road noise.



22811/7016



23891/7016 | 23892/7016

**22811/7016**

**Capacity 1200 kg**

Elasticated solid rubber tyres 200 x 50 mm, blue-grey „trackless“, hubs with ball bearings. Low rolling resistance, easy movement, no road noise.

**Trolleys for standard tigger trains**

**23891/7016**

**23892/7016**

**Capacity 1050 kg**

Suitable for transport on standard tigger trains. Resilient angle steel design with corners supports.

Powder coated in anthracite grey RAL 7016. swivel castors with polyamide wheels 200 x 50 mm white, but 1 castor is electrically conductive, black polypropylene wheel body, hub with precision ball bearings. 2 swivel castors with full locking device in the lead diagonal layout.

Ground clearance: 235 mm



23990



23991

Extra charge for 1 swivel castor with directional locking device instead of 1 swivel castor without locking device.

4 x 90° degrees locking provides good directional stability in longitudinal and transversal direction. Fixed operating lever underneath the frame, not protruding. To be operated from the long side. Easy reach in any castor position.

German patent 10 2016 110 300.4

Special equipment for 23891/7016 and 23892/7016.

Extra charge for 2 swivel castors with fixed locking device operating levers instead of the swivel castors with pivoting operating levers.

Fixed operating levers underneath the frame, not protruding. To be operated from the long side. Easy reach in any castor position. Ground clearance increased to 237 mm, overall height to 282 mm.

Special equipment for 23891/7016 and 23892/7016.

	Order no.	Capacity kg	Platform size L x W mm	For pallet size L x W mm	Outside dimensions L x W x H mm	Loading height mm	Net weight kg
<b>Pallet Dollies</b>	22801/7016	750	1210 x 810	1200 x 800	1255 x 855 x 329	282	34
	22881/7016	1050	1210 x 810	1200 x 800	1255 x 855 x 329	282	33
	22811/7016	1200	1210 x 810	1200 x 800	1255 x 855 x 329	282	35
<b>Trolleys for standard tigger trains</b>	23891/7016	1050	1210 x 810	1200 x 800	1255 x 855 x 327	280	34
	23892/7016	1050	1210 x 1010	1200 x 1000	1255 x 1055 x 327	280	34
	23990			1 swivel castor with directional locking device			
	23991			2 swivel castors with fixed locking device operating levers			



22921/7016

**Stacking frames for pallet dollies**

**22921/7016**

For parking flat pallets and pallet cages at an ergonomically comfortable level. Angle steel construction with catch corners, sturdy tubular supports with base plates. Stable support tubes with foot plates, to be inserted into corner sleeves at the stacking frame. Powder coated, anthracite grey RAL 7016.

Stacking frames can be bolted tight with the pallet dolly via base plates and bolting set (included in delivery).



22892/7016

**Self-locking push handle 22892/7016**

Self-locking push handle for pallet dollies from 800 mm width. For comfortable and ergonomic moving of empty and loaded pallet dollies. Sturdy tubular steel construction with strong support claws. Handle and cross tube with softgrip. In unlocked position movable via two auxiliary rollers.

**Utility patent**  
20 2014 010 367



Example of use

Order no.	Capacity kg	Platform size L x W mm	For pallet size L x W mm	Height mm		Net weight kg
				without pallet dolly	with pallet dolly	
22921/7016	1200	1210 x 810	1200 x 800	370	652	19
22892/7016			Self-locking push handle			7,5

**Mobile tilting stands****3270/7016**

For plastic boxes, steel plate boxes, wire baskets etc., adjustable in height and mobile. Sectional steel-/ tubular construction with steelplate platform. Powder coated anthracite grey RAL 7016. 4 swivel castors with TPE tyres, hubs with bush bearing, 2 wheels with locks.

Steel plate platform with all side rim, 20 mm high. Not inclinable, adjustable in height in intervals of 25mm.

Height adjustable from 720 - 995 mm.

**3270/7016****13580/7016****Euro box rollers**

Compatible for Euro boxes 600 x 400 mm, powder coated anthracite grey RAL 7016. 4 swivel castors with TPE tyres, hubs with groove ball bearing. 2 wheels with locks. Flat packed delivery.

**13580/7016**

Open angle steel construction.

**13540/7016**

Roller with 2 platforms. Both platforms of derived timber material board housed in frames, rim 15 mm high. Clearance between platforms 400 mm. Loading height 194/623 mm. Capacity of upper shelf 100 kg.

**135400/7016**

as 13540/7016, but with tubular push bar. Loading height 194/623 mm.

**1384/7016**

Euro box cart, tubular and sectional steel construction, bolted. Variable use of shelf frames, distance 100 mm, angle when inclined 15° and 30°. Shelf heights: 311, 611, 911, 1211, 1511 mm. Capacity per shelf 80 kg.

With 5 platforms made of derived timber material boards, rim 13 mm high.

**13540/7016****135400/7016****1384/7016**

	Order no.	Capacity kg	Wheel-Ø mm	Platform size L x W mm	Outside dimensions L x W x H mm	Net weight kg
<b>Mobile tilting stands</b>	3270/7016	150	75	605 x 405	605 x 405 x 995	17
<b>Euro box rollers</b>	13580/7016	250	125	605 x 405	605 x 405 x 209	9
	13540/7016	250	125	605 x 408	677 x 414 x 638	17
	135400/7016	250	125	605 x 408	747 x 414 x 970	18
<b>Euro box cart</b>	1384/7016	400	160	1240 x 610	1372 x 685 x 1686	109





8301/7016 - 8303/7016



Reinforcement struts increases the capacity of inserted shelves.



### Shelved trolleys | box carts

Tubular and sectional steel or angle steel, welded and powder coated anthracite grey RAL 7016. 1 fix and 3 or 4 shelves made of special wood material boards, surface grey. Variable use of shelves, in a grid of 100 mm. Capacity per shelf 90 kg. 2 swivel and 2 fixed-wheel castors, TPE tyres 200 x 40 mm, hubs with groove ball bearing.

### Shelved trolleys Modular system

8301/7016 - 8303/7016

Bolted construction. Swivel castors with wheel locks.

### Shelves

Additional charge or price reduction for shelves including 1 pair of support brackets.

Size mm	Order no.
1000 x 600	E8101ETAW/7016
1000 x 700	E8102ETAW/7016
1200 x 800	E8103ETAW/7016

### Reinforcement struts for shelved trolleys

With flanges for two-point screw attachment. 1 pair per trolley is included. Capacity per shelf is 150 kg instead of 90 kg.

If more shelves need to have an increased capacity, please order reinforcement struts correspondingly.

Reinforcement struts 1 additional pair for 1 shelf

Size mm	Order no.
1000 x 600	E8101VK/7016
1000 x 700	E8102VK/7016
1200 x 800	E8103VK/7016



5392/7016 - 5393/7016



Vertical locking rod with turning lever and cylinder lock.



**TOTALSTOP - the fetra central brake system**  
With only one foot the rotation of wheels and the swivelling movement of both swivel castors can be securely locked. The brake pedal is always visible to the operator. Standard with TOTALSTOP.



### Box carts 5392/7016 | 5393/7016

in angle steel construction with tubular handlebar and with 2-leaf door of angle steel with welded wire lattice. Delivery includes 4 shelves. Wire lattice 40 x 40 x 4 mm, completely welded and powder coated anthracite grey RAL 7016.

1 fixed and 4 detachable wood material shelves, surface grey. 2 swivel and 2 fixed-wheel castors with TPE tyres, hubs with groove ball bearing.

### Accessories on pages 183-185

	Order no.	Capacity kg	Platform size L x W mm	Outside dimensions L x W x H mm	Shelf heights mm	Net weight kg
Shelved trolleys	8301/7016	600	1000 x 600	1169 x 609 x 1800	269, 669, 1069, 1469	64
	8302/7016	600	1000 x 700	1169 x 709 x 1800	269, 669, 1069, 1469	69
	8303/7016	600	1200 x 800	1369 x 809 x 1800	269, 669, 1069, 1469	86
Box carts	5392/7016	750	1000 x 680	1170 x 745 x 1792	292, 582, 882, 1182, 1482	144
	5393/7016	750	1200 x 780	1370 x 845 x 1792	292, 582, 882, 1182, 1482	175
Add. shelves	1325/7016			for Box cart 5392/7016		
	1926/7016			for Box cart 5393/7016		

### Tubular steel truck B1330L/7016

Handy tubular steel truck with steel sheet blades, sturdy welded construction, anthracite grey RAL 7016. Safety grips. Steel sheet front shovel mountable, therefore exchangeable. Pneumatic tyres on synthetic rims, hubs with roller bearings. Curved top bar and transversal struts. For safe transport of circular items such as rolls, cans, buckets etc.

With replaceable synthetic rockers.

Flat packed delivery.

**Utility patent**

20 2004 010 071.1



B1330L/7016

	Order no.	Capacity kg	Height mm	Blade length mm	Blade width mm	Total width mm	Pneumatic tyres mm	Net weight kg
Tubular steel truck	B1330L/7016	300	1300	250	320	580	260 x 85	15

➤ Further devices in anthracite grey can be found on the following pages:

#### ➤ Sheet metal dump trucks



Page 121-123

#### ➤ Lifting table carts



Page 171-173

#### ➤ Angle rolls



Page 177